

ROOSEVELT SPECIFICATIONS

Minimum weight: 35 lbs.
Maximum weight: 115 lbs.

Minimum height: 33.5 inches
Maximum height: 62 inches

Shoulder width maximum: 15.5 inches
Thigh width maximum: 14.5 inches

Shoulder strap heights:

- 12.5"
- 15"
- 17.25"
- 19.75"
- 22.25"

Padded seat extenders provide optimum seat depth for each leg. Any combination of depths is available.

Left Leg	Right Leg
12.5"	12.5"
15.5"	15.5"
17.0"	17.0"

Height from seat bottom to seat top is 30 inches.

Our "EZ-Tether" system makes tethering unnecessary in most cases, simplifying the installation in older vehicles.

Ask us how we can customize your Roosevelt!

As always, we accept returns and charge NO restocking fees!

See DEMO VIDEOS:
www.youtube.com/user/MerrittManufacturing



Designed and manufactured in the United States by Merritt Manufacturing, Inc., The Roosevelt™ conforms to all applicable Federal motor vehicle safety standards.

©2016 Merritt Manufacturing, Inc. All Rights Reserved

MERRITT MANUFACTURING, INC.

PO Box 17152
Indianapolis, IN 46217
Phone: 317-409-0148
Fax: 317-893-2567
Email: info@merrittcarseat.com

www.MerrittCarSeat.com
Check us out on social media!



THE ROOSEVELT™
A car seat specially designed for children with special health care needs.



